



产品特性/Product Features

- IP6K9K
- 10A 85°C
- 12-750VDC
- 1000MΩ (1000VDC) , IEC 60664-1
-

触点参数 / Contact parameters

		1a
		4.5mΩ (at 10A)
		10A
		2×10 ⁻⁵
	450V型	750V型
	1000VDC	1000VDC
	100A(320VDC)1	100A(320VDC)1
	4.5kW	7.5kW
1)	1×10 ⁻⁵ 450VDC,10A)	1×10 ⁻⁵ 750VDC,10A)
		10A:
		15A:1h
		20A:20min
		40A:30s
		60A:10s
		100A:0.6s

1) 23°C, 0.6s:5.4s.

2) 85°C, 2.5 mm².

性能参数 / Performance parameters

	1000MΩ(1000VDC)
	3000VAC 1min
	3000VAC 1min
()	≤30ms
()	≤10ms
	196m/s ²
	490m/s ²
	10Hz ~ 500Hz 49m/s ²
	5% ~ 85%RH
	-40°C ~ 85°C
	QC
	150g
	66.8mm×39.0mm×48.2mm

线圈参数 / Coil parameters

VDC	VDC	VDC	W
12	9	1	2.6
24	≤18	≥2	2.6

-40°C ~ 85°C)

外形图、安装孔尺寸 / Outline drawing, mounting hole size

10mm ±0.2mm

10-50 mm

